NWTPA 2009 Rules for garden and farm tractors

General Rules: pull officials reserve the right to modify and enforce safety rules at the pulls!!

Stock Farm Tractors

- 1. Any tractor may qualify in a max (2) classes. One hook per class
- 2. Draw bar must not exceed 21 inches in height. Weights will not be more than 21 inches forward from the fixed front of the tractor (NON-MOVING PARTS). Any weight or part falling off the tractor during the pull shall result in disqualification. Hitches can't be closer than 12 inches from center of housing.
- 3. The tractor weight will include the driver. There will be no weight or driver change after weigh in.
- 4. Drivers will be 14 years or older or have an valid tractor safety operator permit.
- 5. Tractor engines must be STOCK. No turbo unless factory issue for date of tractor.
- 6. Tractors will not exceed 5 mph. except during competition.
- 7. There will be no transmission downshifting during a pull. A restart will be allowed within the first 25 feet.
- 8. Pull will end when the flagger signals to stop!! Hole digging will result in a 25feet penalty.
- 9. No cutting tires.

10. Stock Tractors will not exceed 8 mph.

Super-Stock/Super Farm/Pro Stock Tractors

- 1. There is no limit on tire size, cut tires ok, but no dual tires.
- 2. There is no track speed limit. 5mph maximum off track limit.
- 3. Wheelie bars are required, 2 bars are required on new tractors
- 4. Tractors of any age are welcome
- 5. Kill switch that can be used by sled driver required
- 6. On board fire extinguisher required
- 7. Hitch height requirements same as stock tractors (21") with the following restrictions; 3" opening, 7/8 thickness. No closer than 18" from rear axle.
- 8. Tractor must have working brakes
- 9. Three tractor minimum to hold class, otherwise combine classes.
- 10. Tractor must be no longer than 12ft. from center of rear axle to front most point (open for discussion)

- 11. Rear fenders recommended, required for new tractors 2010 season.
- 12. Electric fans recommended and required for 2010 season.
- 13. Deadman's throttle (spring loaded to return engine to idle) mandatory by 2010
- 14. Engine must be the same make, with the same number of cylinders as issued from the factory.
- 15. Engines may be mounted in any safe manner
- 16. Any safe RPM
- 17. Custom exhaust and intake manifolds/headers ok
- 18. Turbo chargers and super chargers allowed, water injection ok, inter and after coolers ok (limit on number of turbos?)
- 19. Must have shields around turbo and super charger and cross bolts (or other system of stopping turbocharger parts from coming out of the exhaust during a pull) holding exhaust housing in place.
- 20. SFI steel clutch required
- 21. Side shields are required, not less than 1/8" thick, covering from the bottom of the block up to the head.
- 22. General safety rules for the NTPA and PTPA will be recognized
- 23. Roll cage and 5 point harness required
- 24. Helmets and fire suit required

Naturally Aspirated Hot Farm

- 1. There is no limit on tire size, cut tires ok, but no dual tires.
- 2. There is no track speed limit. 5mph maximum off track limit.
- 3. Wheelie bars are required, 2 bars are required on new tractors
- 4. Tractors of any age are welcome
- 5. Kill switch that can be used by sled driver required
- 6. On board fire extinguisher required
- 7. Hitch height requirements same as stock tractors (21") with the following restrictions; 3" opening, 7/8 thickness. No closer than 18" from rear axle.
- 8. Tractor must have working brakes
- 9. Three tractor minimum to hold class, otherwise combine classes.

- 10. Tractor must be no longer than 12ft. from center of rear axle to front most point (open for discussion)
- 11. Rear fenders recommended, required for new tractors 2010 season.
- 12. Electric fans recommended and required for 2010 season.
- 13. Deadman's throttle (spring loaded to return engine to idle) mandatory by 2010
- 14. No age limit on tractors
- 15. Gasoline, propane, or diesel fuel only. No injection of combustion enhancing material (NOx, alcohol, ect,)
- 16. Engine can be any engine made by the original tractor manufacturer for ag and industrial use with same number of cylinders. (I.E. Moline 800, IH 501, 4-741 in Oliver/Massy allowed, ect.) No cubic inch limit, no turbochargers, Detroit engine bowers ok.
- 17. Side shields are required, not less than 1/8" thick, covering from the bottom of the block up to the head.
- 18. Custom exhaust and intake manifolds/headers ok.
- 19. Any safe RPM
- 20. Steel flywheels will be required by the 2010 season for tractors that are running over 30% of stock RPM
- 21. Clutch protection is required, of any reasonable configuration. Transmission blanket recommended and will be required by 2010 season.
- 22. Helmets, fire suits, and roll bars recommended.

Modified Farm Tractors

- 1. There is no limit on tire size, cut tires ok, but no dual tires.
- 2. There is no track speed limit. 5mph maximum off track limit.
- 3. Wheelie bars are required, 2 bars are required on new tractors
- 4. Tractors of any age are welcome
- 5. Kill switch that can be used by sled driver required
- 6. On board fire extinguisher required
- 7. Hitch height requirements same as stock tractors (21") with the following restrictions; 3" opening, 7/8 thickness. No closer than 18" from rear axle.
- 8. Tractor must have working brakes
- 9. Three tractor minimum to hold class, otherwise combine classes.

- 10. Tractor must be no longer than 12ft. from center of rear axle to front most point (open for discussion)
- 11. Rear fenders recommended, required for new tractors 2010 season.
- 12. Electric fans recommended and required for 2010 season.
- 13. Deadman's throttle (spring loaded to return engine to idle) mandatory by 2010
- 14. Limited to one v-8 engine, 1 carburetor only (any size), stock fuel injection, no super or turbo chargers
- 15. NOx injection ok.
- 16. No cubic inch limit
- 17. Must look like a tractor, have at least partial sheet metal and grill
- 18. Gasoline only
- 19. Side shields are required, not less than 1/8" thick, covering from the bottom of the block up to the head.
- 20. Roll bar or roll cage required, seatbelts recommended.
- 21. Helmets required and fire suits are recommended.
- 22. Steel flywheel and bell housing required, transmissions scatter blanket, driveline safety shielding required.
- 23. Wide front end required
- 24. Vertical exit for exhaust recommended and required on new tractors.

Unlimited Modified

- 1. There is no limit on tire size, cut tires ok, but no dual tires.
- 2. There is no track speed limit. 5mph maximum off track limit.
- 3. Wheelie bars are required, 2 bars are required on new tractors
- 4. Tractors of any age are welcome
- 5. Kill switch that can be used by sled driver required
- 6. On board fire extinguisher required
- 7. Hitch height requirements same as stock tractors (21") with the following restrictions; 3" opening, 7/8 thickness. No closer than 18" from rear axle.
- 8. Tractor must have working brakes
- 9. Three tractor minimum to hold class, otherwise combine classes.

- 10. Tractor must be no longer than 12ft. from center of rear axle to front most point (open for discussion)
- 11. Rear fenders recommended, required for new tractors 2010 season.
- 12. Electric fans recommended and required for 2010 season.
- 13. Deadman's throttle (spring loaded to return engine to idle) mandatory by 2010
- 14. We will allow any tractor to pull which passes in the PTPA, NTPA, ect. For unlimited modified rules.

Stock Garden Tractors

- 1. Wheelie bars are mandatory
- 2. Two weight classes: 0-950 lbs. and 951-1200 lbs with driver
- 3. Tires size not to exceed 26" x 12" x 12"
- 4. Hitch height 13 inches max. no closer than 6 inches from center line of rear axle
- 5. Front weights no more than 18 inches in front of center of front axle
- 6. Must have proper engine for model of tractor- same horsepower as original
- 7. Can't have any modifications other than tire size
- 8. The minimum age for this class only is 9 years old and must prove ability to handle lawnmower by passing skills test administered by safety committee. Adult must also walk beside tractor during pull.

Modified Garden Tractor

- 1. Wheelie bars are mandatory
- 2. Weight 1200 lbs. max with driver
- 3. Tire size not to exceed 26"x12"x12"
- 4. Hitch height 15 inches max. no closer than 6 inches from centerline of rear axle
- 5. Front weights no more than 18 inches in front of center of front axle
- 6. No more than 2 cylinder engine from any lawnmower for any chassis and naturally aspirated (no turbo or nitrous)
- 7. 55 inch wheel base max.
- 8. The minimum age for this class only is 14 years old and must prove ability to handle lawnmower by passing skills test administered by safety committee.
- 9. Need to have kill switch

Super Modified Garden Tractors

- 1. Wheelie bars are mandatory
- 2. Weight 2000 lbs. max. with driver
- 3. Tire size not to exceed 31"x15"x15"
- 4. Width of tractor 60 inches max.
- 5. Hitch height 15 inches max, no closer than 6 inches from centerline of rear axle
- 6. Limited to 200 cubic inches
- 7. Must have scatter shield around clutch
- 8. Engine safety plates on sides of block
- 9. Chain shields on all chains at least 12 gauge thick
- 10. Rear fenders and front grill
- 11. Must have appearance of tractor
- 12. Rear mounted kill switch for sled operator and fire extinguisher
- 13. Driver must wear helmet.
- 14. The minimum age for this class only is 14 years old and must prove ability to handle lawnmower by passing skills test administered by safety committee.