

- A. Stock 2 wheel drive under 5500 lbs.
- B. Supper stock 2 wheel drive under 5500lbs.
- C. Stock 4 wheel drive under 4500 lbs.
- D. Stock 4 wheel drive small block under 6000lbs.
- E. Supper stock 4 wheel drive small block under 6000lbs.
- F. Stock 4 wheel drive big block under 6000lbs.
- G. Supper stock 4 wheel drive big block under 6000lbs.
- H. Heavyweight under 8500lbs.
- I. 5800 lbs. country modified

Rules for classes A,C,D,F

1. Truck must have all components front bumper, body, doors, and brakes in working order.
2. Bed must have floor intact. Nothing allowed in bed unless secured
3. All components must be in original position on stock frame.
4. Batteries must be securely fastened down.
5. Seating and steering must be close to stock.
6. Seat belts must be functional and worn. All open cab vehicles must wear helmet
7. Fuel tanks must be securely fastened.
8. Pump fuels only, on alcohol fuels or compressed fluids, such as nitrous or propane.
9. No internal engine modifications allowed and maximum 2 external modifications. (ex. Headers, intake, carburetor)
10. Original style transmission only. Both stick and automatic are fine.
11. Blocked suspension allowed.
12. Tire and rim modifications are allowed. Must be DOT tires, no terra tires, no sharpening or cutting of tires allowed.
13. Ballast is allowed. Weights must be securely fastened on the vehicle and must not exceed 42" in front of center line of front axel. No weights will be allowed in the cab, under the hood or on the sides of the vehicle unless approved by tech inspection. Weights must not interfere with the scales during weigh-in.
14. Maximum height of hitch is 24" to fixed point of hitch. (does not include clevis unless it raises the hitch point) Hitch must be rigid in all directions and solidly mounted to frame. No chains or cables allowed. Hitch breakage will cause for disqualification.

Rules for classes B,E,G

1. Truck must have all components front bumper, body, doors, and brakes in working order.
2. Bed must have floor intact. Nothing allowed in bed unless secured
3. All components must be in original position on stock frame.
4. Batteries must be securely fastened down.
5. Seating and steering must be close to stock.
6. Seat belts must be functional and worn. All open cab vehicles must wear helmet
7. Fuel tanks must be securely fastened.
8. All internal engine modifications allowed and any carb/intake manifold combo allowed (single carb only, naturally aspirated)
9. Original style transmission only. Both stick and automatic are fine.
10. Blocked suspension allowed.
11. Tire and rim modifications are allowed. Must be DOT tires, no terra tires, no sharpening or cutting of tires allowed.
12. Drive shaft loops required for rear only.
13. Ballast is allowed. Weights must be securely fastened on the vehicle and must not exceed 42" in front of center line of front axel. No weights will be allowed in the cab, under the hood or on the sides of the vehicle unless approved by tech inspection. Weights must not interfere with the scales during weigh-in.
15. Maximum height of hitch is 24" to fixed point of hitch. (does not include clevis unless it raises the hitch point) Hitch must be rigid in all directions and solidly mounted to frame. No chains or cables allowed. Hitch breakage will cause for disqualification.

Rules for heavyweight truck class H

1. Truck must have all components front bumper, body, doors, and brakes in working order.
2. Bed must have floor intact. Nothing allowed in bed unless secured
3. All components must be in original position on stock frame.
4. Batteries must be securely fastened down.
5. Seating and steering must be close to stock.
6. Seat belts must be functional and worn. All open cab vehicles must wear helmet
7. Fuel tanks must be securely fastened.
8. All internal engine modifications allowed.
9. Original style transmission only. Both stick and automatic are fine.
10. Blocked suspension allowed.
11. Tire and rim modifications are allowed. Must be DOT tires, no terra tires, no sharpening or cutting of tires allowed.
12. Ballast is allowed. Weights must be securely fastened on the vehicle and must not exceed 42" in front of center line of front axel. No weights will be allowed in the cab, under the hood or on the sides of the vehicle unless approved by tech inspection. Weights must not interfere with the scales during weigh-in.
13. Maximum height of hitch is 24" to fixed point of hitch. (does not include clevis unless it raises the hitch point) Hitch must be rigid in all directions and solidly mounted to frame. No chains or cables allowed. Hitch breakage will cause for disqualification.

5800 lbs. country modified truck class I

If unable to meet the qualification requirements for one of the other classes, the vehicle will be put in this class.